

Product - Data-Sheet

ESBAND Type		HR Elastic 85 black + PU		data-sheet no.
		1st side	2nd side	40002
Carcass		without special carcass		
Coating		TPU ground	polyurethane ground	
Hardness		85 ± 5 Shore A	55 ± 7 Shore A	
Resistance to abrasion		very high	high	
Food approved		no	no	
Coefficient of friction to steel paper		0,4 ± 0,1 μ 0,7 ± 0,1 μ	0,4 ± 0,1 μ 0,8 ± 0,1 μ	
Resistance to temperature		-10 up to + 60 °C		
Antistatic		yes		
Breaking resistance per cm width endless*		-/-		
Elongation at 10 mm width endless*		10 N 20 N 30 N	1,3 up to 1,5 % 3,0 up to 3,4 % 4,8 up to 5,5 %	
Strength required for 1% elongation*		9 ± 2 N		
Minimum pulley diameter*		12 mm		
Available sizes standard		length width thickness	150 up to 2000 mm 3,0 up to 300 mm 1,3 up to 4,0 mm	
Tolerances		length width thickness	± 1,0 % (min. +/- 2,5 mm) ± 0,5 mm ± 0,1 mm	
*at smallest thickness				
All data in this data-sheet correspond to the latest state of the art Modifications are possible without prior notice. The values stated are for information only; they do not guarantee a specific property.				Edition: 28.05.2005