

Product - Data-Sheet

ESBAND Type		HT 4017 + PU		data-sheet no.
		1st side	2nd side	41172
Carcass		aramide special carcass		
Coating		Hytrel® ground	polyurethane ground	
Hardness		40 ± 5 Shore D	55 ± 7 Shore A	
Resistance to abrasion		high	high	
Food approved		no	no	
Coefficient of friction to steel paper		0,5 ± 0,1 μ 0,5 ± 0,1 μ	0,4 ± 0,1 μ 0,8 ± 0,1 μ	
Resistance to temperature		-10 up to + 60 °C		
Antistatic		possible		
Breaking resistance per cm width endless*		2700 N		
Elongation at 10 mm width endless*		300 N 600 N 1000 N	0,2 up to 0,4 % 0,5 up to 0,7 % 0,9 up to 1,2 %	
Strength required for 1% elongation*		1000 ± 50 N		
Minimum pulley diameter*		25 mm		
Available sizes standard		length width thickness	540 up to 4000 mm 5,0 up to 600 mm 1,5 up to 6,0 mm	
Tolerances		length width thickness	± 1,0 % (min. +/- 2,5 mm) ± 0,5 mm ± 0,1 mm	
*at smallest thickness				
All data in this data-sheet correspond to the latest state of the art Modifications are possible without prior notice. The values stated are for information only; they do not guarantee a specific property.				Edition: 25.06.2004