

Product - Data-Sheet

ESBAND Type		NE 133		data-sheet no.
		1st side	2nd side	21300
Carcass		polyester/ cotton special carcass		
Coating		neoprene rubber profiled	textile black	
Hardness		75 ± 5 Shore A	-/-	
Resistance to abrasion		medium	-/-	
Food approved		no	no	
Coefficient of friction to steel paper		0,6 ± 0,1 μ 0,8 ± 0,1 μ	0,2 ± 0,1 μ 0,4 ± 0,1 μ	
Resistance to temperature		-20 up to + 100 °C		
Antistatic		yes		
Breaking resistance per cm width endless*		2100 N		
Elongation at 10 mm width endless*		30 N 300 N 600 N	0,0 up to 0,1 % 0,5 up to 0,7 % 1,6 up to 2,0 %	
Strength required for 1% elongation*		300 ± 30 N		
Minimum pulley diameter*		15 mm		
Available sizes standard		length width thickness	180 up to 4400 mm 3,0 up to 420 mm 1,3 mm	
Tolerances		length width thickness	± 0,5 % (min. +/- 2,5 mm) ± 0,5 mm ± 0,15 mm	
*at smallest thickness				
All data in this data-sheet correspond to the latest state of the art Modifications are possible without prior notice. The values stated are for information only; they do not guarantee a specific property.				Edition: 28.01.2004