

Product - Data-Sheet

ESBAND Type		NE 20/1		data-sheet no.
		1st side	2nd side	22010
Carcass		polyester/ cotton special carcass		
Coating		neoprene rubber profiled	textile raw	
Hardness		75 ± 5 Shore A	-/-	
Resistance to abrasion		medium	-/-	
Food approved		no	no	
Coefficient of friction to steel paper		0,6 ± 0,1 μ 0,8 ± 0,1 μ	0,1 ± 0,1 μ 0,3 ± 0,1 μ	
Resistance to temperature		-20 up to + 100 °C		
Antistatic		yes		
Breaking resistance per cm width endless*		950 N		
Elongation at 10 mm width endless*		100 N	0,4 up to 0,6 %	
		300 N	1,8 up to 2,0 %	
		600 N	5,5 up to 5,9 %	
Strength required for 1% elongation*		190 ± 10 N		
Minimum pulley diameter*		8 mm		
Available sizes standard		length	180 up to 4200 mm	
		width	3,0 up to 420 mm	
		thickness	0,8 mm	
Tolerances		length	± 0,5 % (min. +/- 2,5 mm)	
		width	± 0,5 mm	
		thickness	± 0,15 mm	
*at smallest thickness				
All data in this data-sheet correspond to the latest state of the art Modifications are possible without prior notice. The values stated are for information only; they do not guarantee a specific property.				Edition: 28.01.2004