

# Product - Data-Sheet

ESBAND Type		SNE Elastik		data-sheet no.
		1st side	2nd side	20062
Carcass		without special carcass		
Coating		polyurethane grey ground	polyurethane grey ground	
Hardness		80 ± 5 Shore A	80 ± 5 Shore A	
Resistance to abrasion		high	high	
Food approved		no	no	
Coefficient of friction to	steel paper	0,3 ± 0,1 μ 0,8 ± 0,1 μ	0,3 ± 0,1 μ 0,8 ± 0,1 μ	
Resistance to temperature		-20 up to + 100 °C		
Antistatic		no		
Breaking resistance per cm width endless*		on request		
Elongation at 10 mm width endless*		on request		
Strength required for 1% elongation*		4,8 ± 2 N		
Minimum pulley diameter*		10 mm		
Available sizes standard	length width thickness	200 up to 1500 mm 5,0 up to 300 mm 0,6 up to 3,0 mm		
Tolerances	length width thickness	± 2,0 % (min. +/- 2,5 mm) ± 1,0 mm ± 0,1 mm		
*at smallest thickness				
All data in this data-sheet correspond to the latest state of the art Modifications are possible without prior notice. The values stated are for information only; they do not guarantee a specific property.				Edition: 06.02.2012