

Product Data

GX 1806



Product Description:

Squeeze Belt for separating soft components
GX 1806 is recommended for processing materials with solid parts and sharp particles. Machine driven by a chain drive.

Max Schlatterer
GmbH & Co. KG
Alt-Ulmer-Str. 3
89542 Herbrechtingen
Tel.: +49(0)7324 15-0
Fax.: +49(0)7324 15-280
www.esband.de
info@esband.de

Product Data:

- Tensile Element:** endlessly manufactured, special weave construction
tear resistant, low elongation
- Running Side:** thermoplastic Polyurethane, hardness 90 +- 5 Shore A
surface with small profiles ('X' or 'W' profile)
- Carrying Side:** thermoplastic Polyurethane, hardness 90 +- 5 Shore A
surface with small profiles ('X' or 'W' profile)
- Availability:**
- | | |
|-----------|----------------|
| length | 1300 - 3000 mm |
| width | 150 - 300 mm |
| thickness | 10.0 - 17.0 mm |
- Tolerances:**
- | | |
|-----------|----------|
| length | ± 1.0 % |
| width | ± 0.5 mm |
| thickness | ± 0.2 mm |
- Specification:** nude-colored with sealed edges
coating materials are suitable for food contact in accordance
with FDA regulations and the EU Regulation 10/2011



Advantages:

- highly wear resistant top cover
- very robust belt construction
- surfaces easy to clean
- temperature resistant from -25°C to 80°C
- resistant to oil and grease
- excellent resistance to hydrolysis
- good low-temperature flexibility
- highly resistant to micro-organisms

Statements in this data sheet represent the current technology status. Specifications are subject to change without prior notice.

The given values are for informational purposes only. They do not constitute a warranty of any product properties.

The data sheet does not replace a technical consultation by our technical service. The values stated were measured under laboratory conditions and cannot fully be transferred to operating conditions. Max Schlatterer GmbH & Co.KG do not have any influence on the application and the conditions on site.

Stand: 06.2019