

# Product - Data-Sheet

ESBAND Type	KBL 14		data-sheet no.
Material	Polyamide		60-14.01
Tape thickness <sup>(1)</sup>	0.7 mm		
Surface structure	Tobacco side	rough	
	Running side	rough	
Grip on tobacco	good		
Temperature-resistance	up to 80 °C		
Wear resistance	good		
Air Permeability <sup>(2)</sup>	40 m <sup>3</sup> /h	± 3 m <sup>3</sup> /h	
Breaking strength	550 N/cm	- 8.0 %	
Elongation of endless tape at 150 N/cm pre-tension	0.017	+ 0.3 % - 0.2 %	
Tape widths available	6.2 - 10.2 mm		
Tolerances	length	+ 0 % / - 1 %	
	width	+ 0 mm / - 0.5 mm	
	thickness	+ 0.05 mm / - 0.02 mm	
Recommended for tobacco transport	LOG LOGA SASIB	MARK 10 PASSIM PROTOS	
<small>(1) - Thickness control according to MSN 93.502      (2) - Air permeability control according to MSN 85.001, tape width 9,2 mm All data in this data-sheet correspond to the latest state of the art. Modifications are possible without prior notice. The values stated are for information only; they do not guarantee a specific property.</small>			Edition: 27.01.2017  Copyright ESBAND